

MCR-TI04-P

Datasheet

Document Version : 01

Publication Date : 2026-05-26



1 Product Overview

1.1 Product introduction

The MCR7 series expansion module is an IO module, integrating advanced industry technologies and components, suitable for MCR7 series PLCs.

1.2 Product Appearance



2 Main Information

Range of Product	MCR-TI04-P
Product Or Component Type	RTD sensor input expansion module
Sensor Input Channels	4
Sensor Type	PT100、PT1000、NI100、NI120、NI1000、Cu50、Cu100
Resolution	0.1℃

3 Detail Specification

3.1 Module Specification – Temperature Input

Characteristics	Parameter
Description	RTD sensor input module
Input Channels	4
Rate Power consumption	$\leq 30\text{mA}$ (Full load)
Sensor type	PT100、PT1000、NI100、NI120、NI1000、Cu50、Cu100
Resolution	0.1°C
Max accuracy at ambient 25°C	$\pm 0.5\%$ or $\pm 1^{\circ}\text{C}$, Use the bigger
The influence of measuring temperature (Temperature range: -20°C to 60°C)	◆ Pt100、Pt1000、Ni100、NI120、Ni1000: $\pm 1\%$ of PV or $\pm 1^{\circ}\text{C}$, use the bigger ◆ Cu50、Cu100: $\pm 1\%$ of PV or $\pm 1.5^{\circ}\text{C}$, use the bigger
Connector Type	Screw terminal
Signal type	Electric isolation
Input impedance	$\geq 1\text{M}\Omega$
Sample period	$\leq 100\text{ms/Channel}$
Minimum input	0.1°C
Out of range detection	Available
Wire Broken warning	Available
Input Filter	$0\sim 10\text{S}$ (unit: 0.01s)
Input range	◆ Pt100: $-200\sim 850^{\circ}\text{C}$ ◆ Pt1000: $-200\sim 600^{\circ}\text{C}$ ◆ Ni100: $-60\sim 180^{\circ}\text{C}$ ◆ Ni120: $-60\sim 300^{\circ}\text{C}$ ◆ Ni1000: $-60\sim 180^{\circ}\text{C}$ ◆ Cu50: $-50\sim 150^{\circ}\text{C}$ ◆ Cu100: $-50\sim 150^{\circ}\text{C}$

3.2 Environmental Characteristics

Category	Characteristic
Operating ambient temperature	-10℃~60℃
Storage temperature	-20℃~70℃
Relative humidity	55%~95%, without condensation
Class of pollution	2 (IEC60664)
Class of protection	IP20
Coating	Coated protection, dry film thickness $\geq 20\mu\text{m}$; reinforced dry film thickness $\geq 40\mu\text{m}$
Altitude	Operation: 0m~3,000m Transportation: $\leq 6,000\text{m}$
Seismic performance	5~13.2Hz Amplitude 7mm, 13Hz~100Hz Acceleration 2G, 20 times each in X, Y and Z axes
Impact performance	Semi-positive sine wave, acceleration 15G, duration 11ms, 6 times in each of the X, Y and Z directions

3.3 Electromagnetic Susceptibility

Standard	Method	Item
EN IEC 61000-6-4:2019	CISPR 16-2-1	Conducted Emissions at AC Mains Power Port(150kHz-30MHz)
	CISPR 32	Conducted Emissions at Wired Network Port(150kHz-30MHz)
	CISPR 16-2-3	Radiated Emissions(30MHz-1GHz)
	CISPR 16-2-3	Radiated Emissions(Above 1GHz)
EN IEC 61000-6-2:2019	EN 61000-4-6:2014	Conducted Immunity at AC Mains Power Port(150kHz-80MHz)
	EN 61000-4-6:2014	Conducted Immunity at Signal Port(150kHz-80MHz)
	EN 61000-4-4:2012	Electrical Fast Transients Burst at AC Mains Power Port
	EN 61000-4-4:2012	Electrical Fast Transients Burst at Signal Port
	EN 61000-4-2:2009	Electro static Discharge
	EN 61000-4-8:2010	Power Frequency Magnetic Field
	EN IEC 61000-4-3:2020	Radiated Immunity(80MHz-6GHz)
	EN 61000-4-5:2014+A1:2017	Surge at AC Mains Power Port
	EN 61000-4-5:2014+A1:2017	Surge at Signal Port
	EN IEC 61000-4-11:2020	Voltage Dips and Interruptions

4 Dimension&Installation

4.1 Product Dimension

Definition of Terminals,from top to bottom

MCR-TI04-P	Upper Terminal	A0	B0	B'0	A1	B1	B'1
	Lower Terminal	A2	B2	B'2	A3	B3	B'3

For the meaning of marks , please refer to the table below.

Mark	Meaning
A*	A terminal
B*	B terminal
B'*	B terminal

Dimension: 18*110*75

Unit: mm

